

**TABLE 2: Summary of Significant Assay Results (Eau Claire) (March 6, 2017)**

Type	Drill Hole	From	To	Interval	Gold Assay	Vertical Depth	Interpreted Zone
Infill	ER16-658	<b>341.6</b>	<b>342.1</b>	<b>0.5</b>	<b>20.6</b>	<b>296</b>	450W
		373.5	377.5	4.0	1.95	325	
		incl. 374	376.0	2.0	2.69		
		<b>381.8</b>	<b>393.1</b>	<b>11.3</b>	<b>5.60</b>	<b>336</b>	
		<b>incl. 381.8</b>	<b>384.1</b>	<b>2.3</b>	<b>11.9</b>		
		<b>with 383.5</b>	<b>384.1</b>	<b>0.5</b>	<b>34.6</b>		
		<b>incl. 389.2</b>	<b>393.1</b>	<b>3.9</b>	<b>7.82</b>		
		<b>with 390.0</b>	<b>390.6</b>	<b>0.6</b>	<b>16.8</b>		
	<b>and 392.1</b>	<b>393.1</b>	<b>1.0</b>	<b>17.3</b>			
	433.0	435.0	2.0	8.49	376		
Step-out	ER16-664	220.6	221.2	0.6	6.74	213	450W
		386.5	387.3	0.8	8.56	372	
Step out	ER16-665	71.9	72.5	0.6	8.06	51	450W
Infill	ER16-666	<b>323.8</b>	<b>328.0</b>	<b>4.3</b>	<b>5.37</b>	<b>274</b>	450W
		incl. 323.8	325.4	1.7	8.94		
		and 326.7	327.4	0.7	9.98		
		341.2	344.0	2.8	1.54	287	
		<b>350.0</b>	<b>354.6</b>	<b>4.6</b>	<b>8.95</b>	<b>296</b>	
		<b>incl. 350.0</b>	<b>350.8</b>	<b>0.8</b>	<b>19.4</b>		
	<b>and 352.8</b>	<b>354.6</b>	<b>1.8</b>	<b>20.4</b>			
Infill	ER16-668	<b>327.4</b>	<b>328.3</b>	<b>0.9</b>	<b>20.6</b>	<b>281</b>	450W
		346.8	348.3	1.5	9.93	298	
Infill	ER16-669	<b>251.0</b>	<b>252.0</b>	<b>1.0</b>	<b>23.6</b>	225	450W
		301.0	302.0	1.0	2.75	270	
Step out	ER16-670	58.6	59.1	0.5	3.19	41	450W
		83.2	83.7	0.5	4.46	59	
		87.2	87.7	0.5	5.13	62	
Step out	ER16-671	65.9	67.2	1.3	15.8	46	450W
		incl. 66.4	67.2	0.8	23.2		
Infill	ER17-672	105.6	106.6	1.0	4.05	80	450W
		118.4	119.9	1.5	6.80	90	
		incl. 118.9	119.4	0.5	19.2		
		152.9	153.4	0.5	4.22	115	
Infill	ER17-673	<b>352.0</b>	<b>357.9</b>	<b>5.9</b>	<b>3.63</b>	<b>315</b>	450W
		incl. 352.6	354.0	1.4	9.12		
		and 356.0	357.0	1.0	4.36		
		367.0	367.7	0.7	3.61	326	
		372.0	374.5	2.5	2.86	331	
		<b>373.0</b>	<b>373.5</b>	<b>0.5</b>	<b>10.8</b>	331	
Infill	ER17-674	<b>313.5</b>	<b>326.8</b>	<b>13.3</b>	<b>8.31</b>	<b>233</b>	450W
		<b>incl. 313.5</b>	<b>315.8</b>	<b>2.3</b>	<b>4.28</b>		
		<b>and 318.0</b>	<b>326.8</b>	<b>8.8</b>	<b>11.4</b>		
		<b>335.2</b>	<b>337.7</b>	<b>2.5</b>	<b>11.4</b>	<b>245</b>	
		<b>incl. 335.7</b>	<b>336.2</b>	<b>0.5</b>	<b>45.5</b>		
	410.0	411	1.0	3.65	298		
Infill	ER17-675	84.8	88.6	3.8	1.13	60	450W
		incl. 84.8	85.3	0.5	4.74		
		102.8	103.8	1.0	3.85	71	
Infill	ER17-676					NSV	450W
Infill	ER17-677	153.3	154.3	1.0	3.66	113	450W
Infill	ER17-679	203.5	204.0	0.5	9.34	158	450W
Infill	ER17-680	253.0	256.0	3.0	0.78	198	450W
		324.2	324.7	0.5	2.84	248	
		349.0	349.6	0.6	1.91	265	
		352.7	353.2	0.5	2.17	268	

Type	Drill Hole	From	To	Interval	Gold Assay	Vertical Depth	Interpreted Zone
		379.5	381	1.5	1.20	286	
Infill	ER17-681	130	131	1.0	3.29	89	450W
		<b>134</b>	<b>138.4</b>	<b>4.4</b>	<b>2.59</b>	<b>93</b>	
		<b>incl. 134</b>	<b>134.5</b>	<b>0.5</b>	<b>11.8</b>		
		and 137.4	138.4	1.0	5.50		
		<b>174</b>	<b>185</b>	<b>11.0</b>	<b>3.02</b>	<b>122</b>	
		<b>incl. 179</b>	<b>185</b>	<b>6.0</b>	<b>4.48</b>		
		<b>and 183.5</b>	<b>185</b>	<b>1.5</b>	<b>8.80</b>		
Infill	ER17-690	<b>374.6</b>	<b>375.1</b>	<b>0.5</b>	<b>16.7</b>	<b>353</b>	450W
Infill	ER17-692	238.3	239.3	1.0	6.76	196	450W
		<b>incl. 238.3</b>	<b>238.8</b>	<b>0.5</b>	<b>10.5</b>		
		254.5	255.1	0.6	6.54	208	
		280.6	281.1	0.5	4.15	228	
		306.5	310	3.5	2.64	249	
		incl 307.0	309	2.0	4.08		